



1/2" Thin Brick Flats Dimensions, Weights, and Coverage (Wire Cut*)

Name	Width (W)		Height (H)		Length (L)		Return (R)		Weights		Units/ft ²		Packaging	
	in	mm	in	mm	in	mm	in	mm	lbs	kg	Units/ft ²	Units/M ²	Type	QTY
2 1/4" Modular	1/2	13mm	2 1/4	57	7 5/8	194	-	-	0.7	0.3	6.9	74.3	Box	44
2 1/2" Standard	1/2	13mm	2 1/2	64	8	203	-	-	0.9	0.4	5.7	61.4	Box	44
4" Closure	1/2	13mm	3 5/8	92	7 5/8	194	-	-	1.2	0.5	4.5	48.4	Box	48
2 1/2" Norman	1/2	13mm	2 1/2	64	11 1/2	292	-	-	1.4	0.6	4	43.1	Box	32
3 1/2" Jumbo	1/2	13mm	3 1/2	89	11 1/2	292			1.7	0.8	3	32.3	Box	30

1/2" Thin Brick Corners Dimensions, Weights, and Coverage (Wire Cut*)

Name	Width (W)		Height (H)		Length (L)		Return (R)		Weights		Units/Length		Packaging	
	in	mm	in	mm	in	mm	in	mm	lbs	kg	Units/LF	Units/M ²	Type	QTY
2 1/4" Modular Corner	1/2	13mm	2 1/4	57	7 5/8	194	3 5/8	92	1	0.4	4.5	48.4	Box	20
2 1/2" Standard Corner	1/2	13mm	2 1/2	64	8	203	3 1/2	89	1.1	0.5	4	43.1	Box	20
4" Closure Corner	1/2	13mm	3 5/8	92	7 5/8	194	3 5/8	92	1.5	0.7	3	32.3	Box	32
2 1/2" Norman Corner	1/2	13mm	2 1/2	64	11 1/2	292	3 1/2	89	1.7	0.8	4	43.1	Box	33
3 1/2" Jumbo Corner	1/2	13mm	3 1/2	89	11 1/2	292	3 1/2	89	2.1	1	3	32.3	Box	20

*Note: Product thickness is based on 1/2" wire cut texture thin brick. Smooth brick, tumbled brick, or other textures may be 5/8" or 3/4" thick, which will slightly affect the weights and boxes listed.

The Above Brick Manufactured by H.C. Muddox comply with the following specifications:

ASTM C1088: Grade Exterior or Interior; Type TBS, TBX, or TBA as specified in Purchase Order